

SHENZHEN BRILLIANT CRYSTAL TECHNOLOGIC CO.,LTD.

**深 圳 市 彩 晶 科 技 有 限 公 司**

The specification for the following models :

**CM12864-2SLDAA-5**

<b>PROPOSED BY</b>		<b>APPROVED</b>
Design	Approved	

TEL:+86-755-29995238

FAX:+86-755-29459900

Http://www.cj86.com

E-mail:szcj86@gmail.com

Http://www.szcm-lcd.com


E-mail:szcj86@hotmail.com

地址：深圳市南山区西丽留仙洞工业区顺和达厂区 B 栋

### 1. Mechanical Specification

ITEM	STANDARD VALUE		UNIT
Dot Matrix	128 X 64 DOTS		--
MODULE DIMENSION	93.0 (W) X 70.0 (H) X 14.0 (T)		mm
VIEWING DISPLAY AREA	70.7 (W) X 38.8 (H)		mm
ACTIVE DISPLAY AREA	66.52 (W) X 33.24 (H)		mm
DOT SIZE	0.48 (W) X 0.48 (H)		mm
DOT PITCH	0.04 (W) X 0.04 (H)		mm
DRIVE METHOD	1/64 Duty , 1/9 BIAS		
VIEWING DIRECTION	6 O'clock		
LED Backlight Color	Yellow Green		
Backlight Input	DC +5.0V	V	mA
LED backlight current	35		mA
Backlight Half-Lift Time	35,000		HR.
INPUT VOLAGE	DC +5.0V	V	mA
LCD DRIVER	KS0108		
Weight	83g		

### 2. Mechanical Diagram



## 3. Interface Pin Connections

NO	SYMBOL	LEVEL	FUNCTION
1	VSS	0	Power Ground
2	VDD	5.0V	Power Supply
3	VO	-3V -5V	Voltage for LCD
4	D/I	H/L	D/I= " H ", DB7 DB0 is display DATA D/I= " L ", DB7 DB0 is command
5	R/W	H/L	R/W= " H ", E= " H " data is read to DB7 DB0 R/W= " L ", E= " H L " data is written to IC
6	E	H/L	R/W= " L ", DB7 DB0 is locked at its falling edge.R/W= " H ", E= " H " DDRAM data is read to DB7 DB0
7	DB0	H/L	DATA BUS
8	DB1	H/L	DATA BUS
9	DB2	H/L	DATA BUS
10	DB3	H/L	DATA BUS
11	DB4	H/L	DATA BUS
12	DB5	H/L	DATA BUS
13	DB6	H/L	DATA BUS
14	DB7	H/L	DATA BUS
15	CS1	H/L	H:Chip Selection for IC1
16	CS2	H/L	H:Chip Selection for IC2
17	RST	H/L	Chip Reset signal
18	VEE	-5V	Negative Voltage for LCD driver
19	LEDA	--	LED(+5V)
20	LEDK	--	LED(0V)

## 4. Absolute Maximum Ratings

ITEM	SYMBOL	MIN.	TYPE	MAX.	UNIT
OPERATING TEMPERATURE	TOP	0/-20	--	+50/+70	
STORAGE TEMPERATURE	TST	-10/-30	--	+60/+80	
INPUT VOLAGE	VI	4.75	5.0	5.25	V
SUPPLY VOLTAGE FOR LOGIC	VDD-VSS	--	5.0	5.5	V
SUPPLY VOLTAGE FOR LCD	VDD-VO	--	--	9.5	V
STATIC ELECTRICITY	Be sure that you are grounded when handing LCM.				